Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-090-4499

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.141 inches

**Body Length:** 

0.156 inches

**Body Width:** 

### 0.594 inches

**Body Height:** 

## 0.766 inches

Actuator Type:

## Integral knob

# Effective Electrical Rotation In Deg Angular Rotation:

260.0

# Maximum Starting Torque:

2.00 inch-ounces

# Maximum Running Torque:

2.00 inch-ounces

# Maximum Stop Torque:

48.00 inch-ounces

# Center To Center Distance Between Terminals:

0.344 inches

## **Fragility Factor:**

Moderately rugged

### **Terminal Location:**

Lower adjacent side two rows

### **Mounting Method:**

Terminal

# Center To Center Distance Between Terminal Rows:

0.156 inches

### **Features Provided:**

Humidity proof

## **Cubic Measure:**

0.071 cubic inches

# **Electrical Resistance Per Section:**

500.0 ohms c and better flooring

# **Rotary Actuator Travel In Angular Deg:**

260.0



Center To Center Distance Between Center Terminal And Outside Terminal: 0.172 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.125 7th secondary quality **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0