NSN 5905-01-090-5327

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-090-5327 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.200 inches **Body Length:** 0.240 inches **Body Width:** 0.390 inches **Body Height:** 0.360 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-01-090-5327

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No