Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-091-0090

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.050 inches

- **Body Length:**
- 1.000 inches

Body Width:

0.180 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 4320.0 and 6480.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

0.750 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

2.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 4320.0 and 6480.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-27208/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0