Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-1181

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

### **Electrical Resistance:**

30.000 kilohms

### **Resistance Tolerance In Percent:**

-5.000/+5.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

16

# Terminal Type:

Pin

### Reliability Indicator:

Not established

### Terminal Length:

Between 0.125 inches and 0.150 inches

### **Body Length:**

0.830 inches

#### Body Width:

Between 0.240 inches and 0.305 inches

#### **Body Height:**

0.200 inches

Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

1.500 total network

#### **Identical Value Resistor Quantity:**

15 each resistor

#### Style Designator:

Dual inline

### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-83401/2 government specification

## Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0