NSN 5905-01-091-4540

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-4540

Onestina Oceantitus
Section Quantity:
Body Style:
Rectilinear, slide control
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.560 inches
Body Length:
4.000 inches
Body Width:
0.625 inches
Body Height:
0.770 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Longitudinal Actuator Travel:
2.75 inches
Longitudinal Actuator Effective Electrical Stroke Length:
2.750 inches
Mounting Facility Quantity:
4
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 significant section

70.0 single section

NSN 5905-01-091-4540

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0