NSN 5905-01-091-5876

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-5876 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.594 inches **Mounting Bushing Length:** 0.188 inches **Body Length:** 0.320 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 230.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5905-01-091-5876

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0