Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-5876

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.594 inches

#### Mounting Bushing Length:

0.188 inches

**Body Length:** 

0.320 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

230.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Tab

## **Electrical Resistance Per Section:**

1.000 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

290.0

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 tab, solder lug

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5905-01-091-5876

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

