Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-7283

# Section Quantity:

1

**Body Style:** 

Cylindrical

# **Reliability Indicator:**

Not established

# **Body Diameter:**

0.625 inches

# **Body Length:**

0.250 inches

# Actuator Type:

Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

260.0

#### **Terminal Location:**

# Rear end

**Mounting Method:** 

Tab

#### **Electrical Resistance Per Section:**

500.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

260.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.2 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

#### **Actuator Travel Control Feature:**

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

# Standard Taper Curve Per Section:

A single section

# **Terminal Type And Quantity:**

3 turret

# Shelf Life:

N/a

# Unit Of Measure:

#### **Demilitarization:**

No

# NSN 5905-01-091-7283

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

