NSN 5905-01-091-7890

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-7890 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7000 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.030 inches **Shaft Length:** 0.750 inches **Body Length:** 0.681 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.10 inch-ounces **Maximum Running Torque:** 0.10 inch-ounces **Shaft End Play:** 0.003 inches

Shaft Runout: 0.001 inches

NSN 5905-01-091-7890

Precision Wire Wound Variable Resistor - Page 2 of 2



| Lateral Runout: |
|---|
| 0.002 inches |
| Pilot Diameter Runout: |
| 0.0015 inches |
| Shaft Radial Play: |
| 0.002 inches |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 350.0 |
| Function Conformity Tolerance Per Section: |
| -3.00/+3.00 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Precious Material And Location: |
| Terminals gold |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0