NSN 5905-01-091-7891

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-091-7891 **Section Quantity: Reliability Indicator:** Not established **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 275.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 6.00 inch-ounces **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A002a0