NSN 5905-01-091-9897

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-091-9897 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 1.000 inches **Body Diameter:** 0.594 inches **Body Length:** 0.312 inches **Overall Diameter:** 0.594 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 230.0 **Maximum Starting Torque:** 7.00 inch-ounces **Maximum Running Torque:** 7.00 inch-ounces **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Threaded stud **Rotary Actuator Travel In Angular Deg:** Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

NSN 5905-01-091-9897

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0