NSN 5905-01-092-1550

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-092-1550

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: -200.0/+200.0 Electrical Resistance: 910.000 ohms Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating in Watts:
Electrical Resistance: 910.000 ohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.500 Inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
910.000 ohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Tempinal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Tempinal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Encased Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
1.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
1.500 inches Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Body Diameter: 0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
0.090 inches Body Length: 0.300 inches Power Dissipation Rating In Watts:
Body Length: 0.300 inches Power Dissipation Rating In Watts:
0.300 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39017/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No
A001a0
Fiig: