Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-092-1559

Section Quantity:

2

Body Style:

Cylindrical bushing mounted **Reliability Indicator:**

Not established

Terminal Length:

Between 1.313 inches and 1.375 inches

Body Diameter:

0.687 inches

Shaft Diameter:

Between 0.077 inches and 0.079 inches

Shaft Length:

Between 0.463 inches and 0.525 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.000 inches

Shaft Style:

Round, slotted, flat undercut

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

Between 0.180 inches and 0.300 inches

Terminal Location:

Right adjacent side two rows

Mounting Method:

Clamp

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better industrial clears

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.050 inches and 0.071 inches

Power Dissipation Rating Per Section In Watts:

1.00 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0