NSN 5905-01-092-5724

Motor Driven Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-092-5724

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Body Diameter:
1.380 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.810 inches
Mounting Bushing Length:
0.310 inches
Body Length:
4.910 inches
Shaft Style:
Round
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Motor Type:
Servo
Mounting Method:
Clamp ring and standard bushing
Electrical Resistance Per Section:
16.5 kilohms single section
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
0.6 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Function Characteristic Per Section:
Single section linear
Err Default:

NSN 5905-01-092-5724

Motor Driven Variable Resistor - Page 2 of 2



Motor Voltage Type And Rating In Volts:

100.0 dc

Precious Material And Location:

Tab, solder lug terminal surfaces gold

Terminal Type And Quantity:

3 tab, solder lug and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A502h0