Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-092-7608

Section Quantity:
1
Reliability Indicator: Not established
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation: 275.0
Maximum Starting Torque: 2.00 inch-ounces
Maximum Running Torque: 2.00 inch-ounces
Maximum Stop Torque:
6.00 inch-ounces Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0