

View Online at https://aerobasegroup.com/nsn/5905-01-092-9680

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Overall Length:

0.855 inches

Terminal Length:

0.187 inches

Overall Height:

0.437 inches

Overall Width:

0.190 inches

Shaft Diameter:

0.100 inches

Shaft Length:

0.060 inches

Body Length:

0.795 inches

Body Width:

0.190 inches

Body Height:

0.250 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7200.0

Center To Center Distance Between Terminals:

0.500 inches

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Cubic Measure:

0.038 cubic inches

NSN 5905-01-092-9680

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 50.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 7200.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.200 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0