

View Online at https://aerobasegroup.com/nsn/5905-01-093-8431

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Overall Length:

7.276 inches

Overall Height:

0.315 inches

Overall Width:

0.190 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

NSN 5905-01-093-8431

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Location | |
|----------------------|--|
| Rear end | |
| Mounting Method: | |
| Terminal and unthr | eaded hole |
| Electrical Resista | nce Per Section: |
| 5.000 percent, rate | ed amperes c and better flooring |
| Rotary Actuator T | ravel In Angular Deg: |
| Between 6120.0 an | nd 9720.0 |
| Ambient Tempura | ture In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single sectior | n |
| Fempurature Coef | fficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -250.0/+250.0 singl | e section |
| Power Dissipatior | Rating Per Section In Watts: |
| 0.75 7th secondary | quality |
| Resistance Tolera | nce Per Section In Percent: |
| -10.0/+10.0 single s | section |
| Actuator Travel Co | ontrol Feature: |
| Clutch | |
| Ambient Tempura | ture In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section | |
| Standard Taper C | urve Per Section: |
| A single section | |
| Test Data Docume | ent: |
| 31349-mil-r-39035 | specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| iormat; excludes c | ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and | performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And | d Quantity: |
| 3 wire lead | |
| Specification Data | |
| 81349-mil-r-39035/ | 1 government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A002a0 | |