NSN 5905-01-093-8434

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-093-8434

Section Oceantifus
Section Quantity:
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.469 inches
Terminal Length:
0.500 inches
Overall Height:
1.125 inches
Overall Width:
0.625 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.594 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
2.50 inch-ounces
Maximum Running Torque:
2.50 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:

0.362 inches

NSN 5905-01-093-8434

Center To Center Distance Between Terminals:

0.200 inches

3 pin

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Fragility Factor: Moderately rugged **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:** Humidity proof **Cubic Measure:** 0.232 cubic inches **Electrical Resistance Per Section:** 25.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 300.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0/+5.0 -55 degrees celsius single section and -3.0/+3.0 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Square pin terminals **Terminal Type And Quantity:**

NSN 5905-01-093-8434

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0