

View Online at <https://aerobasegroup.com/nsn/5905-01-094-1752>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

0.535 inches

Overall Height:

0.500 inches

Overall Width:

0.187 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.078 inches

Shaft Length:

0.035 inches

Body Length:

0.500 inches

Body Width:

0.187 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 7200.0 and 15120.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Cubic Measure:

0.047 cubic inches

Electrical Resistance Per Section:

10.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 7200.0 and 15120.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0