Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-094-1757

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Body Length:

0.161 inches

Body Width:

0.405 inches

Body Height:

0.405 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

220.0

Maximum Starting Torque:

2.70 inch-ounces

Maximum Running Torque:

2.70 inch-ounces

Maximum Stop Torque:

6.90 inch-ounces

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Features Provided:

Humidity proof

Electrical Resistance Per Section:

100.000 ohms c and better flooring

Rotary Actuator Travel In Angular Deg:

220.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

70.0 single section

Power Dissipation Rating Per Section In Watts:

0.2 7th secondary quality

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0