## NSN 5905-01-094-7182

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-094-7182 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** Between 0.927 inches and 0.947 inches **Shaft Diameter:** Between 0.146 inches and 0.166 inches **Shaft Length:** Between 0.469 inches and 0.531 inches **Body Length:** Between 0.443 inches and 0.463 inches **Shaft Style:** Round, slotted, knurled **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Terminal Location:** Front end **Mounting Method:** Tab **Electrical Resistance Per Section:** 10.0 megohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a

## NSN 5905-01-094-7182

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A002a0