Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-095-2573

Section	Quantity:

1

Body Style:

Rectangular

Terminal Length:

0.172 inches

Shaft Diameter:

0.075 inches

Shaft Length:

0.080 inches

- **Body Length:**
- 0.375 inches
- Body Width:
- 0.190 inches
- Body Height:

0.375 inches

- Shaft Style:
- Round, slotted
- Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

4780.0

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Right adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

4780.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section



Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-27208/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A002a0