NSN 5905-01-095-3953

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-095-3953 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.180 inches **Body Diameter:** 0.385 centimeters **Body Length:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 190.0 **Maximum Starting Torque:** 6.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Rugged **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 20.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section

Stops

Actuator Travel Control Feature:

NSN 5905-01-095-3953

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

