Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-096-2327

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.844 inches

Overall Height:

1.131 inches

Overall Width:

0.844 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.969 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

22.50 inch-ounces

Maximum Running Torque:

22.50 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 9 oclock



Nonturn Device Radius: 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Double pole, single throw, one open, one closed **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Right-left adjacent sides **Mounting Method:** Standard bushing **Features Provided:** Switch **Cubic Measure:** 0.379 cubic inches **Electrical Resistance Per Section:** 2.500 kilohms single section **Rotary Actuator Travel In Angular Deg:** 300.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.5 120 degrees celsius single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Switch Current Type And Rating In Amps: 2.000 ac **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity:

7 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0