NSN 5905-01-096-2327

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-096-2327 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.844 inches **Overall Height:** 1.131 inches **Overall Width:** 0.844 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.969 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round Switch Type: **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 22.50 inch-ounces **Maximum Running Torque:** 22.50 inch-ounces **Maximum Stop Torque:**

Nonturn Device Location:

64.00 inch-ounces

At 9 oclock

NSN 5905-01-096-2327

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.531 inches
Switch Operating Position: Start of rotation
Switch Contact Arrangement:
Double pole, single throw, one open, one closed
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Right-left adjacent sides
Mounting Method:
Standard bushing
Features Provided:
Switch
Cubic Measure:
0.379 cubic inches
Electrical Resistance Per Section:
2.500 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and -2.5/+2.5 85 degrees celsius single
section and +0.0/+5.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:

7 tab, solder lug

A single section

Terminal Type And Quantity:

NSN 5905-01-096-2327

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0