## NSN 5905-01-096-3044

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-096-3044 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.991 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.890 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.480 inches **Body Length:** 1.100 inches **Overall Diameter:** 1.187 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 351.0 **Maximum Starting Torque:** 

0.50 inch-ounces

**Maximum Running Torque:** 

0.50 inch-ounces

## NSN 5905-01-096-3044

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.684 cubic inches
Electrical Resistance Per Section:
6.000 percent, rated amperes c and better finish
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
15.0 1st section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary finish
Function Conformity Per Section:
All sections absolute linearity
Fixed Tap Quantity Per Section:
1 1st section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation 1st section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion

All sections linear

**Function Characteristic Per Section:** 

## NSN 5905-01-096-3044

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 all sections	
Terminal Type And Quantity:	
7 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	

No

Fiig:

A002a0

Demilitarization: