Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-096-7944

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.625 inches

Body Length:

0.562 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.500 kilohms single section

Rotary Actuator Travel In Angular Deg:

312.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 eyelet

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0