Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-096-9842

#### Section Quantity:

1

Body Style:

Cylindrical servo mounted

### **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.7810 inches

#### **Pilot Length:**

0.0620 inches

#### **Undercut Diameter:**

0.750 inches

#### **Undercut Width:**

0.0570 inches

#### **Body Diameter:**

0.875 inches

## Shaft Diameter:

Shart Diameter.

0.1248 inches

## Shaft Length:

0.480 inches

#### Body Length:

1.100 inches

## Mounting Lip Diameter:

0.8750 inches

#### Mounting Lip Depth:

0.0620 inches

#### **Undercut Diameter:**

0.117 inches

#### Shaft Style:

Round, stepped

#### Shaft Bearing Type:

Ball

### Actuator Type:

Double ended shaft

## Effective Electrical Rotation In Deg Angular Rotation:

336.0

#### Maximum Starting Torque:

0.50 inch-ounces

#### Shaft End Play:

0.00500 inches

#### Shaft Runout:

0.001 inches

# NSN 5905-01-096-9842

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.00100 inches Shaft Radial Play: 0.001 inches Undercut Length: 0.110 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 6.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section absolute linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 150.0 single section **Function Characteristic Per Section:** Single section table Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Special Features:** Resistor has a dummy cup **Test Data Document:** 89305-484605 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

## NSN 5905-01-096-9842

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0