## NSN 5905-01-097-1684

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-097-1684
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
2.000 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.250 inches and 0.350 inches
Body Length:
0.305 inches
Body Width:
Between 0.365 inches and 0.385 inches
Body Height:
0.075 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.325 total network
Identical Value Resistor Quantity:
13 each resistor
Unpackaged Unit Weight:
0.5 grams
Style Designator:
Flat pack
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/3 government specification

## NSN 5905-01-097-1684

Film Fixed Resistor Network - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0