

View Online at <https://aerobasegroup.com/nsn/5905-01-097-9866>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

2.8750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

2.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

3.250 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Body Length:

3.070 inches

Mounting Lip Diameter:

3.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

4.50 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better select

Rotary Actuator Travel In Angular Deg:

360.0

Resistance Temperature Characteristic Range Per Section In Percent:

-5.0/+5.0 -65 degrees celsius all sections and -5.0/+5.0 125 degrees celsius all sections

Function Conformity Tolerance Per Section:

-0.50/+0.50 2nd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

2.25 7th secondary finish

Function Conformity Per Section:

2nd section absolute conformity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

8 oclock single primary

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Special Features:

One fixed film resistor internally mtd ea cup

Test Data Document:

10001-3274207 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0