NSN 5905-01-098-1505

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-098-1505 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 1.225 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Effective Electrical Rotation In Deg Angular Rotation:**

Shaft Length: 0.625 inches **Body Length:** 0.600 inches **Overall Diameter:** 2.376 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft 350.0 **Maximum Starting Torque:** 0.30 inch-ounces **Maximum Running Torque:** 0.25 inch-ounces

NSN 5905-01-098-1505

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00500 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.186 cubic inches
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:

3 turret

NSN 5905-01-098-1505

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarization:

No

Fiig:

A002a0