

View Online at <https://aerobasegroup.com/nsn/5905-01-098-2074>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.920 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.125 inches

Shaft Length:

3.670 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.250 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round, v channelled

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

240.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

80.00 inch-ounces

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

2.500 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

280.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Shaft grooved 0.250 in. From end of shaft to bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0