## NSN 5905-01-098-4060

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-098-4060

Section Overther
Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.135 inches
Body Length:
0.298 inches
Body Width:
0.434 inches
Body Height:
0.360 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
0.10 inch-ounces
Center To Center Distance Between Terminals:
0.300 inches
Fragility Factor:
Rugged
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
25.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.150 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:

Stops

## NSN 5905-01-098-4060

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No