NSN 5905-01-098-8548

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-098-8548

Tourness Conflictent Of Booleton on In Book Book Day Orleins
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-250.0/+250.0
Electrical Resistance:
150.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
Not rated
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Not rated
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+105.0
Inclosure Method:
Encapsulated
Terminal Quantity:
5
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.130 inches and 0.150 inches
-
Between 0.130 inches and 0.150 inches
Between 0.130 inches and 0.150 inches Body Length:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity: 4 each resistor
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity: 4 each resistor Style Designator:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Shelf Life:
Between 0.130 inches and 0.150 inches Body Length: 0.600 inches Body Width: 0.110 inches Body Height: 0.320 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 0.400 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Shelf Life: N/a

No

NSN 5905-01-098-8548

Film Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0