

View Online at <https://aerobasegroup.com/nsn/5905-01-098-8550>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.500 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.700 inches

Mounting Bushing Length:

0.312 inches

Body Length:

0.305 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

0.20 inch-ounces

Maximum Running Torque:

0.20 inch-ounces

Maximum Stop Torque:

80.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.187 inches

Shaft End Play:

0.006 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Hermetically sealed

Electrical Resistance Per Section:

2.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

330.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0