Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-099-9496

view Online at https://aerobasegroup.com/nsi//3505-01-055-3450
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.312 inches
Body Length:
0.750 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Shaft End Play:
0.010 inches
Shaft Runout:
0.003 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.003 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0



Terminal Location:	
Radially positioned over less the	nan half the circumference
Mounting Method:	
Standard bushing	
Electrical Resistance Per Se	ction:
200.0 ohms single section	
Rotary Actuator Travel In An	gular Deg:
3600.0	
Function Conformity Tolerar	ice Per Section:
-0.25/+0.25 single section	
Ambient Tempurature In Deg	Celsius Per Section At Zero Percent Rated Power:
125.0 single section	
Power Dissipation Rating Pe	r Section In Watts:
2.0 free air single section	
Function Conformity Per Sec	ction:
Single section independent line	earity
Resistance Tolerance Per Se	ection In Percent:
-5.0/+5.0 single section	
Actuator Travel Control Feat	ure:
Stops	
Function Characteristic Per	Section:
Single section linear	
Tempurature Coefficient Of F	Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section	
Ambient Tempurature In Deg	Celsius Per Section At Full Rated Power:
70.0 single section	
Precious Material And Locat	ion:
Terminal surfaces gold	
Precious Material:	
Gold	
Terminal Type And Quantity:	:
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	