## NSN 5905-01-100-3980

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-100-3980 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.270 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Starting Torque:** 1.60 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Mounting Facility Quantity: Mounting Method:** Clamp **Electrical Resistance Per Section:** 50.000 ohms c and better finish Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 2nd section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 65.0 all sections

Terminal Type And Oue

**Terminal Type And Quantity:** 

3 turret

## NSN 5905-01-100-3980

Precision Wire Wound Variable Resistor - Page 2 of 2



Sneit	Lite:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0