NSN 5905-01-101-0098

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-101-0098

Electrical Resistance: 10.000/s1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s175.0 Tempurature Method: Tempurature Method: Tempurature Method: Tempurature Method: Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/s175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 157.0 Tempurature Range Of	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4.1000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.150/175.0 Tempurature Range Of	-25.0/+25.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.010 30dy Diameter: 1.056 inches 30dy Length: 1.050 inches 70wer Dissipation Rating In Watts: 1.050 free air 8tyle Designator: 1.0xial terminal each end Test Data Document: 1.0xial terminal each end Test Data Document: 1.0xial terminal each end Test Data Document: 1.0xial terminal each end Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain inviviconmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.010 30dy Diameter: 1.050 inches 30dy Length: 1.050 inches 30dy Length: 1.050 free air Style Designator: Ixial terminal each end Test Dato Document: 1349-milr-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain invivronmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	61.900 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.010 1.02 1.03 1.04 1.05 1.05 1.05 1.05 1.05 1.05 1.05 1.05	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Tempurature Method	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Istablished Reliability Failure Rate Level In Percent: Incologo John State Comment Reliability Failure Rate Level In Percent: Incologo John State Comment Inc	Ambient Tempurature In Deg Celsius At Full Rated Power:
Trempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 3.040 Diameter: 0.055 inches 3.040y Diameter: 0.055 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain specification (includes requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Rody Diameter: 0.056 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: xixial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Rody Diameter: 0.065 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: 0.048 beignator: 0.049 Designator: 0.051 beignator: 0.052 beignator: 0.053 inches 0.056 free air 0.056 free air 0.057 free air 0.058 free air 0.058 beignator: 0.058 beign	175.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Rody Diameter: 0.065 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Reliability Englare Rate end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 8.00dy Diameter: 0.065 inches 8.00dy Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Skyle Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	-55.0/+175.0
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Redy Diameter: 0.065 inches Redy Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Rely Length: 0.050 free air Rely Length: 0.051 free air Rely Length: 0.052 free air Rely Length: 0.053 free air Rely Length: 0.054 free air Rely Length: 0.055 free air Rely Length: 0.056 free air 0.057 free air	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Rody Diameter: 0.065 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Reliability Failure Rate Level In Percent: 0.150 inches Power Dissipation Rating In Watts: 0.150 inches Rody Length: 0.150 inches Ro	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Rody Diameter: 0.065 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Reliability Failure Rate Level In Percent: 0.086 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Reliability Failure Rate Level In Percent: 0.086 inches Rody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air 0.05	Terminal Type:
Reliability Failure Rate Level In Percent: 0.010 3ody Diameter: 0.065 inches 3ody Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a	Wire lead
Reliability Failure Rate Level In Percent: 2.010 3.040 Diameter: 2.055 inches 3.040 Length: 2.150 inches 2.067 Power Dissipation Rating In Watts: 2.050 free air 3.151 Designator: 3.152 Data Document: 3.15349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 3.1545 Elife: 3.1756 Shelf Life: 3.1757 Shelf Life:	Reliability Indicator:
Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Established
Body Length: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Reliability Failure Rate Level In Percent:
3.065 inches 3.045 inches 3.050 inches 3.050 inches 3.050 free air 3.050 free air 3.050 free air 3.051 designator: Axial terminal each end 3.051 feet Data Document: 3.051 appendix of the process of th	0.010
Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 0.1349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Body Diameter:
Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.065 inches
Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Body Length:
O.050 free air Style Designator: Axial terminal each end Fest Data Document: B1349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.150 inches
Axial terminal each end Fest Data Document: B1349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.050 free air
Test Data Document: B1349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Style Designator:
81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Axial terminal each end
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	Shelf Life:
Jnit Of Measure:	N/a
	Unit Of Measure:
-	
Demilitarization:	Demilitarization:
No.	No
iig:	Fiig:
A001a0	A001a0