NSN 5905-01-101-0129

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-101-0129

25 0/425 0 Electrical Resistance: 4 020 kilohms Resistance Tolerance in Percent: -0 500/40 500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125 0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175 0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55 0/4175 0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Diameter: 0.056 inches Body Length: 0.150 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Awal terminal each end Test Data Document: 81349-mil-7-51827' specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 4.020 kilohms Resistance Tolerance in Percent:	
4.020 kilohms Resistance Tolerance in Percent: -0.500/40.500 Ambient Tempurature in Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -175.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+175.0 Inclosure Method:	
Resistance Tolerance in Percent: -0.500/+0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0f+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-551827 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.056 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Na Unit Of Measure: - Demilitarization: No Flig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.056 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-milk-551827 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Diameter: 0.066 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-551827 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	·
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.055 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.056 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-551827 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	·
Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Diameter: 0.065 inches Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Length: 0.150 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
O.150 inches Power Dissipation Rating In Watts: O.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
O.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
O.050 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Axial terminal each end Test Data Document: 81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55182/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
No Fiig:	
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	
A001a0	A001a0