NSN 5905-01-101-2747

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-101-2747

Seedien Overstitus
Section Quantity:
Body Style:
Cylindrical bushing mounted
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.313 inches
Body Length:
1.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.000 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Criticality Code Justification:
Zzzy
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:

3 turret

NSN 5905-01-101-2747

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Reference	Number	Differentiating	Characteristic	٠.
7616161166	NULLING	Dilletellianin	Cital acteristic	<i>,</i> 3.

Material will be in accordance with ships parts control cen	ter activity hx quality control	, manufacturing and testing specifications
Shelf Life:		

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0