## NSN 5905-01-101-7036

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-101-7036

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -150.0/+150.0  |
| Electrical Resistance:   |
| 0.010 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Heat Sink Material:  |
| Aluminum alloy   |
| Heat Sink Length:  |
| 6.000 inches   |
| Heat Sink Width:   |
| 4.000 inches   |
| Heat Sink Height:  |
| 2.000 inches   |
| Heat Sink Thickness:   |
| 0.040 inches   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
|  |
| -55.0/+275.0   |
| -55.0/+275.0 Inclosure Method:   |
|  |
| Inclosure Method:  |
| Inclosure Method: Encased  |
| Inclosure Method: Encased Terminal Type:   |
| Inclosure Method: Encased Terminal Type: Tab, solder lug   |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator:  |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established  |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent:   |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010   |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length:  |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches   |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches Body Length:  |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches Body Length: 0.750 inches                                       |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches Body Length: 0.750 inches Body Width:                           |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches Body Length: 0.750 inches Body Width: 0.445 inches              |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.312 inches Body Length: 0.750 inches Body Width: 0.445 inches Body Height: |

10.000 heat sink

**Power Dissipation Rating In Watts:** 

## NSN 5905-01-101-7036

A001a0

Wire Wound Fixed Resistor - Page 2 of 2



| Mounting Hole Size:  |
|--|
| 0.093 inches   |
| Style Designator:  |
| Axial terminal (s)   |
| Test Data Document:  |
| 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |