

View Online at <https://aerobasegroup.com/nsn/5905-01-101-7743>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.165 inches

Shaft Diameter:

0.095 inches

Shaft Length:

0.060 inches

Body Length:

Between 0.740 inches and 0.760 inches

Body Width:

Between 0.180 inches and 0.200 inches

Body Height:

Between 0.240 inches and 0.260 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.490 inches and 0.510 inches

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

Between 0.190 inches and 0.210 inches

Features Provided:

Humidity proof

Cubic Measure:

0.040 cubic inches

Electrical Resistance Per Section:

2.0 megohms single section

Rotary Actuator Travel In Angular Deg:

5400.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.190 inches and 0.210 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

1.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0