## NSN 5905-01-101-7745

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-101-7745

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.735 mils and 0.765 centimeters
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.859 inches and 0.891 inches
Mounting Bushing Length:
Between 0.365 inches and 0.395 inches
Body Length:
Between 0.220 inches and 0.280 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 245.0 and 255.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.370 inches and 0.380 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference

## NSN 5905-01-101-7745

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.110 cubic inches
Electrical Resistance Per Section:
250.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 285.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 eyelet
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0