Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-102-0301

#### Section Quantity:

1

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.7500 inches

#### **Pilot Length:**

0.0620 inches

#### **Undercut Diameter:**

0.750 inches

#### **Undercut Width:**

0.0620 inches

#### **Body Diameter:**

#### 0.875 inches

Shaft Diameter:

#### 0.1248 inches

Shaft Length:

### 0.375 inches

Body Length:

# 0.475 inches

Mounting Lip Diameter:

0.8700 inches

#### Mounting Lip Depth:

0.0620 inches

#### Shaft Style:

Round

#### Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

320.0

#### Maximum Starting Torque:

0.27 inch-ounces

#### Maximum Running Torque:

0.27 inch-ounces

#### Shaft End Play:

0.00500 inches

#### Shaft Runout:

0.001 inches

# NSN 5905-01-102-0301

Precision Nonwire Wound Variable Resistor - Page 2 of 3



# Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.00100 inches **Shaft Radial Play:** 0.001 inches Mechanical Backlash In Deg Angular Rotation: 0.1 **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Cubic Measure:** 0.286 cubic inches **Electrical Resistance Per Section:** 6.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section absolute linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section table Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 89305-485278 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:**

3 turret

#### Shelf Life:

N/a

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0