## NSN 5905-01-102-6397

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-102-6397 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 1.875 inches **Body Length:** 1.580 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.40 inch-ounces **Maximum Running Torque:** 0.30 inch-ounces **Shaft End Play:** 0.003 inches

**Shaft Runout:** 0.001 inches

## NSN 5905-01-102-6397

Lateral Runout: 0.003 inches

0.0015 inches

**Shaft Radial Play:** 

**Pilot Diameter Runout:** 

Precision Wire Wound Variable Resistor - Page 2 of 3



0.002 inches **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.05/+0.05 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops **Tap Location From Ccw Terminal Per Section In Ohms:** 1000.0 single section **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 4 turret

## NSN 5905-01-102-6397

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0