NSN 5905-01-102-6399

Section Quantity:

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-102-6399

Cylindrical bushing mounted
Reliability Indicator:
Not established
Terminal Length:
Between 0.120 inches and 0.122 inches
First Flat Length:
0.430 inches
Flat Height:
0.114 inches
Body Diameter:
0.500 inches
Shaft Diameter:
Between 0.122 inches and 0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.540 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 292.0 and 298.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces
Nonturn Device Location:
At 4'30 oclock and at 10'30 oclock
Nonturn Device Radius:
0.245 inches
Center To Center Distance Between Terminals:
0.200 inches
Screw Thread Diameter:
0.250 inches

NSN 5905-01-102-6399

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef Control of the C
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 292.0 and 298.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single
section and +0.0/+3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
single section
Ferminal Type And Quantity:
3 pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0