NSN 5905-01-102-7316

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-102-7316

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-200.0/+200.0
Electrical Resistance:
4.700 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.120 inches
0.120 inches Body Length:
Body Length:
Body Length: Between 0.740 inches and 0.780 inches
Body Length: Between 0.740 inches and 0.780 inches Body Width:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width: Between 0.015 inches and 0.020 inches
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 13 each resistor
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 13 each resistor Unpackaged Unit Weight:
Body Length: Between 0.740 inches and 0.780 inches Body Width: Between 0.240 inches and 0.280 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 1.750 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 13 each resistor Unpackaged Unit Weight: 1.000 grams

N/a

NSN 5905-01-102-7316

Film Fixed Resistor Network - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A001a0