Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-103-3233

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.165 inches

Shaft Diameter:

0.095 inches

Shaft Length:

Between 0.045 inches and 0.075 inches

Body Length:

Between 0.740 inches and 0.760 inches

Body Width:

Between 0.180 inches and 0.200 inches

Body Height:

Between 0.240 inches and 0.260 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.490 inches and 0.510 inches

End Application:

An/tsc-62a

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

Between 0.090 inches and 0.110 inches

Electrical Resistance Per Section:

10.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.190 inches and 0.210 inches

Power Dissipation Rating Per Section In Watts:

0.75 free air single section



Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

3 pin

Specification Data:

96238-41000450 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0