Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-103-4153

Section Quantity:

1

Body Style:

Rectangular w/bushing

**Reliability Indicator:** 

Not established

Shaft Diameter:

0.067 inches

Shaft Length:

0.280 inches

Mounting Bushing Length:

0.218 inches

Body Length:

0.500 inches

Body Width:

## 0.200 inches

**Body Height:** 

0.187 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Screw Thread Diameter:

0.125 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

44.0

**Terminal Location:** 

Rear end

Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

2.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

3600.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.3 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0