NSN 5905-01-103-5555

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-103-5555

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.859 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
292.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Mechanical Backlash In Deg Angular Rotation:
1.5
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.000 kilohms single section
Rotary Actuator Travel In Angular Deg:

312.0

NSN 5905-01-103-5555

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A002a0